

# Technical Specification



Gasketed plate-and-frame heat exchanger

Date: **Thursday, April 3, 2025**

Type: **T8-BFM-134**  
Article number: **T8-BFM-134**

Alfa Laval Industrial line are gasketed plate-and-frame heat exchangers available in a variety of designs suitable for practically all types of industrial application for heating and cooling. A large product range and flexible configuration makes it possible to get a good fit for the applications. The units have high energy efficiency, easy installation and are easy to open for inspection and cleaning.

The Alfa Laval Industrial line Gasketed plate-and-frame heat exchangers are produced in accordance with the quality management system ISO 9001, the environmental management system ISO 14001 and the European Pressure Equipment Directive 2014/68/EC. AutoCAD drawings, 3D models and accessories are available as options.

|                                |                     |
|--------------------------------|---------------------|
| Capacity (kW):                 | <b>250 kW</b>       |
| Temp primary side (°C):        | <b>14 → 9 °C</b>    |
| Temp. secondary side (°C):     | <b>7 → 12 °C</b>    |
| Flow rate primary side (kg/h): | <b>42840,0 kg/h</b> |
| Max. Pressure Drop (kPa):      | <b>20 kPa</b>       |
| Depth (mm):                    | <b>1160 mm</b>      |
| Width (mm):                    | <b>400 mm</b>       |
| Height (mm):                   | <b>890 mm</b>       |
| Weight (kg):                   | <b>303,3 kg</b>     |