

# Technical Specification



Gasketed plate-and-frame heat exchanger

Date: **Thursday, December 18, 2025**

Type: **TL3-BFG-95**  
Article number: **TL3-BFG-95**

Alfa Laval Industrial line are gasketed plate-and-frame heat exchangers available in a variety of designs suitable for practically all types of industrial application for heating and cooling. A large product range and flexible configuration makes it possible to get a good fit for the applications. The units have high energy efficiency, easy installation and are easy to open for inspection and cleaning.

The Alfa Laval Industrial line Gasketed plate-and-frame heat exchangers are produced in accordance with the quality management system ISO 9001, the environmental management system ISO 14001 and the European Pressure Equipment Directive 2014/68/EC. AutoCAD drawings, 3D models and accessories are available as options.

|                                  |                     |
|----------------------------------|---------------------|
| Capacity (kW):                   | <b>150 kW</b>       |
| Temp primary side (°C):          | <b>95 → 57 °C</b>   |
| Temp. secondary side (°C):       | <b>55 → 93 °C</b>   |
| Flow rate primary side (kg/h):   | <b>3397,00 kg/h</b> |
| Flow rate secondary side (kg/h): | <b>3398,00 kg/h</b> |
| Max. Pressure Drop (kPa):        | <b>20 kPa</b>       |
| Depth (mm):                      | <b>620 mm</b>       |
| Width (mm):                      | <b>190 mm</b>       |
| Height (mm):                     | <b>790 mm</b>       |
| Weight (kg):                     | <b>86,40 kg</b>     |